



**12855 VALLEY BRANCH LANE  
FARMERS BRANCH, TX 75234  
TEL: 972.866.0880  
FAX: 972.866.0893**

**RBC - COPYLINE PRODUCTS  
PLAIN PAPER, XEROGRAPHIC,  
AND LASER APPLICATIONS**

**Confidential Price L  
Effective April 1, 20**

#### CARTON

- \*Specifically engineered, die-cut carton
- \*Clam-style
- \*Extra padding to sustain shock
- \*Flute direction changed
- \*Board strength - ECT40 (42#klawhite/26# medium/57#high performance liner)
- Edge crush test (ECT)

#### CORE

PROPERTIES: .188 wall (+/-5%), Inside Diameter 3.021 (+.010";-0.06"), Length is Nominal (+0;-1/32")

#### PHYSICAL REQUIREMENTS

- \*Blade Cut
- \*High-control curing
- \*Brown outside ply, taped to core
- \*Black outside ply, no tape

#### SHIPPING

We take pride in our products and want our customers to have as few problems as possible. Our rolls are stacked on end to prevent crushed cores and/or media during the shipping process.

We also use Corrugated Pallet Tops to protect when double stacked.

TL - Truck Load-FOB Delivered at 40,000 lbs.

LTL - FOB shipping point

**The following printers are compatible with our Copy Line Products:**

**PRINTER COMPATIBILITY:**

**3M:** 609, 659, 1640, 7436, 7736

**C4/Ozalid:** HR324, Mark II, 3036, 3650, 3660, 4037, 4038, 4800, 5025, 5804,  
6030, 6036, 6080, 6090, 6710, 6720, 6800, 7036, 7810, 7820, 7800,  
7850, 8036, 8800, 8820, 8855

**Calcomp:** Solus 4 (Models 54436 & 54424)

**Dietzgen:** 636S, 636SR

**Graphic Enterprises:** Zoomer Q 205, Zoomer 10 Plus

**Ideal/Diato:** SB61, SZ920

**Indigo:** 536

**JDL:** 3000E, 3500E, 5000E

**JRL:** 1220D, 1220E

**KIP/Shacoh:** 920, DP-AIZ, DP-36, DP-3630, KIP 7090, DP-3610, DP-4200

KIP 1030, KIP 1800, KIP 1880, KIP 2710, KIP 2900, KIP 2950, KIP 3400

KIP 2800, KIP 3800, KIP 3620, KIP 3820, KIP 4290, KIP 7090, KIP 9010

KIP 9810, KIP 9820, KIP 9900, Screen 36, Mark II, Starprint 3000

**Mita:** DC-1824/1842F, DC-3648, DC-3648R, Q-205, 10-Plus, Xi-3648

**Océ/ Océ/Bruning:** 3200, 3210, 7000, 7050, 7055, 7056, 7100, 7150, 7200,

7300, 7350, 7360, 7500, 7500S, 7600, 7700, 7700D, 900, 905, 9050

910, 9150, 9036, 9400, 9535, 9555, 9575, 9600, 9700, 9800

**Regma USA:** 910, 914, 915, 916, 925, 9640, 9650, 9660

**Repro CAD:** 50, 200

**Ricoh:** FW740, FW750, FW760, FW810, FW830, FW870

**Xerox:** 990, 2020, 2030, 2080, 2510, 2515, 2520, 3001, 3030, 3050, 3060,

3080, 3090, 5080, 7080, 7085, ES 8180, 8810, 8825, 8830, 8836,

8840, 8845, ES 8150, 8855

**RB-20 lb. 92 Bright**

**PROPERTIES:** 20 lb./75 gsm, Opacity ≥ 88%, Brightness ~ 92, Core size is 3.0" and is available

TTC (Taped to core)

**BEST PRINTING:** Remember to always print on the preferred side of the media. The

preferred side is always on the outside of the roll unless otherwise noted. Handle print media by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° F and 25-70% humidity.

**STORAGE:** Always store laser/xerographic media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print

Our 20lb. Premium bond is the media of choice of high volume plotting and duplicating. It's certainly the best value when archivability is not needed. The bright white base provides high contrast, and the surface finish is optimized for all Laser, LED and xerographic plotters and duplicators.

| <b>BOND</b>                                      | <b>Part No.</b> | <b>Size</b> | <b>Carton</b> | <b>POUNDS<br/>per Carton</b> | <b>Cartons<br/>per Pallet</b> |
|--|-----------------|-------------|---------------|------------------------------|-------------------------------|
| <b>CARTONS - 20 lb. Bond, 92 Bright, 3" core</b> | RB08            | 8.5" x 500' | 4/ctn         | 23                           | 42                            |
|  | RB11            | 11" x 500'  | 4/ctn         | 29                           | 42                            |
|  | RB12            | 12" x 500'  | 4/ctn         | 31                           | 42                            |
|  | RB15            | 15" x 500'  | 4/ctn         | 44                           | 21                            |
|  | RB17            | 17" x 500'  | 4/ctn         | 44                           | 21                            |
|  | RB18            | 18" x 500'  | 4/ctn         | 48                           | 21                            |
|  | RB22            | 22" x 500'  | 2/ctn         | 29                           | 42                            |
|  | RB24            | 24" x 500'  | 2/ctn         | 31                           | 42                            |
|  | RB24-1          | 24" x 500'  | 1/ctn         | 16                           | 35                            |
|  | RB24-250        | 24" x 250'  | 2/ctn         | 16                           | 35                            |
|  | RB28            | 28" x 500'  | 2/ctn         | 36                           | 21                            |
|  | RB30            | 30" x 500'  | 2/ctn         | 39                           | 21                            |
|  | RB30-1          | 30" x 500'  | 1/ctn         | 20                           | 35                            |
|  | RB30-250        | 30" x 250'  | 2/ctn         | 20                           | 35                            |
|  | RB31            | 31" x 500'  | 2/ctn         | 39                           | 21                            |
|  | RB32            | 32" x 500'  | 2/ctn         | 40                           | 21                            |
|  | RB34            | 34" x 500'  | 2/ctn         | 44                           | 21                            |
|  | RB36            | 36" x 500'  | 2/ctn         | 47                           | 21                            |
|  | RB36-1          | 36" x 500'  | 1/ctn         | 24                           | 35                            |
|  | RB36-150        | 36" x 150'  | 4/ctn         | 32                           | 35                            |
| RB36-250   | 36" x 250'      | 2/ctn       | 24            | 35                           |                               |

|   |           |             |       |    |    |
|---|-----------|-------------|-------|----|----|
| <b>CARTONS- 20 lb. Bond, 92 Bright, 3" core<br/>Taped to Core</b> | RB08-T    | 8.5" x 500' | 4/ctn | 23 | 42 |
|   | RB11-T    | 11" x 500'  | 4/ctn | 29 | 42 |
|   | RB12-T    | 12" x 500'  | 4/ctn | 31 | 42 |
|   | RB15-T    | 15" x 500'  | 4/ctn | 44 | 21 |
|   | RB17-T    | 17" x 500'  | 4/ctn | 44 | 21 |
|   | RB18-T    | 18" x 500'  | 4/ctn | 48 | 21 |
|   | RB20-T    | 20" x 500'  | 2/ctn | 28 | 42 |
|   | RB22-T    | 22" x 500'  | 2/ctn | 29 | 42 |
|   | RB24-T    | 24" x 500'  | 2/ctn | 31 | 42 |
|   | RB24-T250 | 24" x 250'  | 2/ctn | 16 | 35 |
|   | RB30-T    | 30" x 500'  | 2/ctn | 39 | 21 |
|   | RB30-T150 | 30" x 150'  | 2/ctn | 12 | 35 |
|   | RB30-T250 | 30" x 250'  | 4/ctn | 20 | 35 |
|   | RB34-T    | 34" x 500'  | 2/ctn | 44 | 21 |
|   | RB36-T    | 36" x 500'  | 2/ctn | 47 | 21 |
|   | RB36-T150 | 36" x 150'  | 4/ctn | 24 | 35 |
|   | RB36-T250 | 36" x 250'  | 2/ctn | 15 | 35 |

|   |          |            |         |      |   |
|---|----------|------------|---------|------|---|
| <b>TUBS - 20 lb. Bond, 92 Bright, 3" core</b> | RB11-B   | 11" x 500' | 105/tub | 782  | 1 |
|   | RB17-B   | 17" x 500' | 70/tub  | 798  | 1 |
|   | RB18-B   | 18" x 500' | 70/tub  | 815  | 1 |
|   | RB22-B   | 22" x 500' | 35/tub  | 512  | 1 |
|   | RB24-B   | 24" x 500' | 35/tub  | 560  | 1 |
|   | RB30-B   | 30" x 500' | 35/tub  | 700  | 1 |
|   | RB34-B   | 34" x 500' | 35/tub  | 807  | 1 |
|   | RB36-B   | 36" x 500' | 35/tub  | 840  | 1 |
|   | RB24-B44 | 24" x 500' | 44/tub  | 704  | 1 |
|   | RB30-B44 | 30" x 500' | 44/tub  | 880  | 1 |
|   | RB36-B44 | 36" x 500' | 44/tub  | 1056 | 1 |

| <b>BOND</b> | <b>Part No.</b> | <b>Size</b> | <b>Carton</b> | <b>POUNDS</b>     | <b>Cartons</b>    |
|-------------|-----------------|-------------|---------------|-------------------|-------------------|
|             |                 |             |               | <b>per Carton</b> | <b>per Pallet</b> |
|             | RB12650         | 12" x 650'  | 108/tub       | 871               | 1                 |
|             | RB15650         | 15" x 650'  | 72/tub        | 725               | 1                 |
|             | RB17650         | 17" x 650'  | 72/tub        | 812               | 1                 |
|             | RB18650         | 18" x 650'  | 36/tub        | 859               | 1                 |
|             | RB22650         | 22" x 650'  | 36/tub        | 720               | 1                 |
|             | RB24650         | 24" x 650'  | 36/tub        | 745               | 1                 |
|             | RB30650         | 30" x 650'  | 36/tub        | 777               | 1                 |
|             | RB36650         | 36" x 650'  | 36/tub        | 933               | 1                 |

| <b>TUBS - 20 lb. Bond, 92 Bright, 3" core</b> | <b>Part No.</b> | <b>Size</b> | <b>Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|---|-----------------|-------------|---------------|--------------------------|---------------------------|
| <b>Taped to core</b>                          | RB24-BT         | 24" x 500'  | 35/tub        | 560                      | 1                         |
|   | RB30-BT         | 30" x 500'  | 35/tub        | 700                      | 1                         |
|   | RB34-BT         | 34" x 500'  | 35/tub        | 735                      | 1                         |
|   | RB36-BT         | 36" x 500'  | 35/tub        | 840                      | 1                         |

| <b>CARTONS - 20 lb. Bond, 92 Bright, 3" core</b> | <b>Part No.</b> | <b>Size</b> | <b>Rolls per</b> | <b>Pounds per</b> | <b>Cartons</b>    |
|--|-----------------|-------------|------------------|-------------------|-------------------|
|  |                 |             | <b>Carton</b>    | <b>Carton</b>     | <b>per Pallet</b> |
|  | RB18650-S       | 18" x 650'  | 1/ctn            | 16.5              | 36                |
|  | RB24650-S       | 24" x 650'  | 1/ctn            | 22                | 36                |
|  | RB30650-S       | 30" x 650'  | 1/ctn            | 28                | 36                |
|  | RB36650-S       | 36" x 650'  | 1/ctn            | 33                | 36                |

| <b>CARTONS - 20 lb. Bond, 92 Bright, Sheets</b> | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|---|-----------------|-------------|-------------------------|--------------------------|---------------------------|
|   | SB1218          | 12" x 18"   | 2000/ctn                | 47                       | 24                        |
|   | SB1722          | 17" x 22"   | 1000/ctn                | 40                       | 24                        |
|   | SB1824          | 18" x 24"   | 1000/ctn                | 47                       | 24                        |
|   | SB2234          | 22" x 34"   | 500/ctn                 | 40                       | 24                        |
|   | SB2436          | 24" x 36"   | 500/ctn                 | 47                       | 24                        |
|   | SB3042          | 30" x 42"   | 300/ctn                 | 27                       | 20                        |
|   | SB3444          | 34" x 44"   | 200/ctn                 | 32                       | 20                        |
|   | SB3648          | 36" x 48"   | 200/ctn                 | 37                       | 20                        |

| <b>CARTONS - 20 lb. Bond, Colors</b> | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|--------------------------------------|-----------------|-------------|-------------------------|--------------------------|---------------------------|
|                                      | RB18-BLU        | 18" x 500'  | 4/ctn                   | 47                       | 21                        |
|                                      | RB24-BLU        | 24" x 500'  | 2/ctn                   | 31                       | 42                        |
|                                      | RB30-BLU        | 30" x 500'  | 2/ctn                   | 39                       | 21                        |
|                                      | RB36-BLU        | 36" x 500'  | 2/ctn                   | 47                       | 21                        |
|                                      | RB18-CAN        | 18" x 500'  | 4/ctn                   | 47                       | 21                        |
|                                      | RB24-CAN        | 24" x 500'  | 2/ctn                   | 31                       | 42                        |
|                                      | RB30-CAN        | 30" x 500'  | 2/ctn                   | 39                       | 21                        |
|                                      | RB36-CAN        | 36" x 500'  | 2/ctn                   | 47                       | 21                        |
|                                      | RB18-GRN        | 18" x 500'  | 4/ctn                   | 47                       | 21                        |
|                                      | RB24-GRN        | 24" x 500'  | 2/ctn                   | 31                       | 42                        |
|                                      | RB30-GRN        | 30" x 500'  | 2/ctn                   | 39                       | 21                        |
|                                      | RB36-GRN        | 36" x 500'  | 2/ctn                   | 47                       | 21                        |
|                                      | RB18-PNK        | 18" x 500'  | 4/ctn                   | 47                       | 21                        |
|                                      | RB24-PNK        | 24" x 500'  | 2/ctn                   | 31                       | 42                        |
|                                      | RB30-PNK        | 30" x 500'  | 2/ctn                   | 39                       | 21                        |
|                                      | RB36-PNK        | 36" x 500'  | 2/ctn                   | 47                       | 21                        |

| <b>TUBS - 20 lb. Bond, Colors</b> | <b>Part No.</b> | <b>Size</b> | <b>Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|-----------------------------------|-----------------|-------------|---------------|--------------------------|---------------------------|
|                                   | RB30650-BLU     | 30" x 650'  | 36/tub        | 725                      | 1                         |
|                                   | RB36650-BLU     | 36" x 650'  | 36/tub        | 871                      | 1                         |
|                                   | RB30650-CAN     | 30" x 650'  | 36/tub        | 725                      | 1                         |
|                                   | RB36650-CAN     | 36" x 650'  | 36/tub        | 871                      | 1                         |
|                                   | RB30650-GRN     | 30" x 650'  | 36/tub        | 725                      | 1                         |
|                                   | RB36650-GRN     | 36" x 650'  | 36/tub        | 871                      | 1                         |
|                                   | RB30650-PNK     | 30" x 650'  | 36/tub        | 725                      | 1                         |
|                                   | RB36650-PNK     | 36" x 650'  | 36/tub        | 871                      | 1                         |

**RB-HB 20 lb. 96 Bright**

**Properties:** 20 lb./ 75 gsm, Opacity ≥ Brightness ~ 96, Core is 3.0" and is available TTC (taped to core)

**Best Printing:** Remember to always print on the preferred side of the media. The preferred

side is always on the outside of the roll unless otherwise noted. Handle print media by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° F and 25-70% humidity.

**Storage:** Always store laser/xerographic media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**Archiving:** 20# Premium Bond is a wood pulp product and is not suitable for long term archival purposes.

Our 20lb. Premium bond is the media of choice of high volume plotting and duplicating. It's certainly the best value when archivability is not needed. The bright white base provides high contrast, and the surface finish is optimized for all Laser, LED and xerographic plotters and duplicators.

|  | Part No. | Size       | Rolls per Carton | Pounds per Carton | Cartons per Pallet |
|--|----------|------------|------------------|-------------------|--------------------|
| <b>CARTONS - 20 lb. Bond, 96 Bright, 3" core</b>                   | RB24-HB  | 24" x 500' | 2/ctn            | 31                | 42                 |
|  | RB30-HB  | 30" x 500' | 2/ctn            | 39                | 21                 |
|  | RB34-HB  | 34" x 500' | 2/ctn            | 45                | 21                 |
|  | RB36-HB  | 36" x 500' | 2/ctn            | 47                | 21                 |
| <b>CARTONS - 20 lb. Bond, 96 Bright, 3" core<br/>Taped to core</b> | RB24-HBT | 24" x 500' | 2/ctn            | 31                | 42                 |
|  | RB30-HBT | 30" x 500' | 2/ctn            | 39                | 21                 |
|  | RB34-HBT | 34" x 500' | 2/ctn            | 45                | 21                 |
|  | RB36-HBT | 36" x 500' | 2/ctn            | 47                | 21                 |

**RTB - 18 LB. Translucent Bond**

**Geometry: 300 & 500 ft. lengths.** Widths vary 11" to 36". Core size is 3.0" and is available TTC (Taped to Core)

**Properties:** 18 lb./68 gsm, Opacity ≥ 69%, Brightness ~ 83.

**Best Printing:** Remember to always print on the preferred side of the media. The preferred side is always on the outside of the roll unless otherwise noted. Handle print media by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° F and 25-70% humidity.

**Storage:** Always store laser/xerographic media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print

**Archiving:** 18# Translucent Bond is a wood pulp product and is not suitable for long term archival purposes.

The economical combination of Translucency and brightness make 18lb. Translucent bond ideal for diazo reproduction and stacked sheetrans on your Laser, LED, or Xerographic plotter/duplicator. The brightness of the sheet provides high contrast, and the surfaces smoothly optimized for your las

|   | Part No. | Size       | Rolls per Carton | Pounds per Carton | Cartons per Pallet |
|---|----------|------------|------------------|-------------------|--------------------|
| <b>CARTONS - 18 lb. Trans Bond, 3" core</b> | RTB18    | 18" x 500' | 2/ctn            | 24                | 42                 |
|   | RTB22    | 22" x 500' | 2/ctn            | 29                | 21                 |
|   | RTB24    | 24" x 500' | 2/ctn            | 31                | 21                 |
|   | RTB30    | 30" x 500' | 2/ctn            | 39                | 42                 |
|   | RTB34    | 34" x 500' | 2/ctn            | 45                | 42                 |
|   | RTB36    | 36" x 500' | 2/ctn            | 47                | 42                 |
| <b>CARTONS - 18 lb. Trans Bond, Sheets</b>  | ST2436   | 24" x 36"  | 500/ctn          | 50                | 24                 |

**RV-20lb, Transparentized Vellum**

**Geometry:** 500 ft. Lengths. Widths vary 11" to 36". Core size is 3.0" and is available

TTC (taped to core)

**Properties:** 20 lb. / .75 gsm, Opacity ≥ 50%

**Best Printing:** Remember to always print on the preferred side of the media. The preferred side is always on the outside of the roll unless otherwise noted. Handle print media by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° F and 25-70% humidity.

**Storage:** Always store laser/xerographic media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**Archiving:** 20# Transparentized Vellum is produced from 15% cotton fiber.

Modern technology has created our awesome laser/LED vellum. Our 100% cotton fiber base is transparentized with environmentally friendly solvents, and surface treatment is applied to produce an extremely smooth faced sheet with excellent pickup and minimal solvent migration. Lines and graphics come out clear, sharp, and dense. 100% cotton means that our vellum will stand up to long term archiving needs.

|  | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|--|-----------------|-------------|-------------------------|--------------------------|---------------------------|
| <b>CARTONS - 20 lb. Vellum, 3" core</b>      | RV17            | 17" x 500'  | 4/ctn                   | 33                       | 21                        |
|  | RV18            | 18" x 500'  | 4/ctn                   | 48                       | 21                        |
|  | RV24            | 24" x 500'  | 2/ctn                   | 31                       | 42                        |
|  | RV30            | 30" x 500'  | 2/ctn                   | 39                       | 21                        |
|  | RV34            | 34" x 500'  | 2/ctn                   | 44                       | 21                        |
|  | RV36            | 36" x 500'  | 2/ctn                   | 47                       | 21                        |
| <b>CARTONS - 20 lb. Vellum, 3" core. TTC</b> | RV17-T          | 17" x 500'  | 4/ctn                   | 44                       | 21                        |
|  | RV18-T          | 18" x 500'  | 4/ctn                   | 48                       | 21                        |
|  | RV24-T          | 24" x 500'  | 2/ctn                   | 31                       | 42                        |
|  | RV30-T          | 30" x 50'   | 2/ctn                   | 39                       | 21                        |
|  | RV34-T          | 34" x 500'  | 2/ctn                   | 44                       | 21                        |
|  | RV36-T          | 36" x 500'  | 2/ctn                   | 47                       | 21                        |

**RF - 4 Mil Double Matte Film**

**Geometry:** 125 ft. lengths. Widths vary 18" to 36". Core size is 3.0"

**Properties:** 4.0 mil, Opacity ≥ 40%

**Best Printing:** Remember to always print on the preferred side of the media. The preferred side is always on the outside of the roll unless otherwise noted. Handle print media by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° F and 25-70% humidity.

**Storage:** Always store laser/xerographic media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**Archiving:** 4 mil Double Matte Laser Film is produced from 100% synthetic polyester and is well suited for long term archival in moderate environmental conditions.

Our double matte film is created from dimensionally stable polyester film held to tight tolerances. The coated surface offers exceptional toner adhesion for Laser, LED and Xerographic plotter/duplicators on both sides. Images can be erased using a FC #79 eraser. Heavyweight 4 mil base is durable and archivable. Low opacity makes it excellent for Diazo masters.

| <b>FILM / MYLAR</b>                             | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|---|-----------------|-------------|-------------------------|--------------------------|---------------------------|
| <b>4 Mil Double Matte Film, 3" core, Carton</b> | RF18            | 18" x 150'  | 2/ctn                   | 18                       | 40                        |
|   | RF24            | 24" x 150'  | 1/ctn                   | 12                       | 40                        |
|   | RF30            | 30" x 150'  | 1/ctn                   | 15                       | 40                        |
|   | RF34            | 34" x 150'  | 1/ctn                   | 16                       | 40                        |
|   | RF36            | 36" x 150'  | 1/ctn                   | 18                       | 40                        |
|   | RF36-300        | 36" x 300'  | 1/ctn                   | 36                       | 40                        |



**RBC-JET LINE PRODUCTS**  
**CAD INK JET & GRAPHIC**  
**INK JET APPLICATIONS**

**CONFIDENTIAL PRI**  
**EFFECTIVE APRIL 1**

CARTON

- \*Specifically engineered, die-cut carton
- \*Clam-style
- \*Extra padding to sustain shock
- \*Flute direction changed
- \*Board Strength - ECT40 (42#klawhite/26#medium/57#high performance liner)  
Edge crush test (ECT)

CORE

PROPERTIES: .80 wall (+/-5%), Inside Diameter 2.002 (+.010"; - 0.06"), Length is Nominal (+0; -1/32")

PHYSICAL REQUIREMENTS:

- \*Blade cut
- \*Date coded printed on inside ply in black ink
- \*Rough side out (outer ply)

The end of roll tab is now removable. I hope allows you to distinguish your product from others in the industry that are just selling price.

Because we take pride in our products and want our customers to have as few problems as possible, our rolls are stacked on end to prevent crushed cores and/or media during the shipping process.

We also use Corrugated Pallet Tops to protect when double stacked.

TL - Truck Load - FOB Delivered at 40,000 lbs.

LTL - FOB Dallas

**The following printers are compatible with our Jet Line Products:**

**PRINTER COMPATIBILITY:**

**Hewlett Packard:** 200, 250c 600, 650c, 350c, 455c, 488ca, 750c, 755cm, 750c Plus, 1050c, 1055cm, 500, 800

**Calcomp:** TechJet

**Encad:** NovaJet I, II, III, IV, NovaPro 36/50, Chroma 24"

**Xerox:** 2230ij

**RIJB - 20 lb. Monochrome Inkjet Bond**

**GEOMETRY:** 150 ft. and 300 ft. lengths. Widths vary 17" to 36". Core size is 2.0"

**PROPERTIES:** 20 lb./ 75 gsm, Opacity ≥ 85%, Brightness ~ 92.

**BEST PRINTING:** Remember to always print on the preferred side of the media. The preferred side is always on the outside of the roll unless otherwise noted. Handle print media by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° and 25-70% humidity.

**STORAGE:** Always store inkjet media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**ARCHIVING:** 203 Inkjet Bond is a wood pulp product and is not suitable for long term archival purposes.

Smooth and opaque 20# inkjet bond paper is the perfect choice for everyday cad plotting. Our product's combination of performance and economy create outstanding value day in and day out. It is available in a variety of widths and core configurations to fit any modern inkjet plotter.

| <b>BOND</b>                            | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|--|-----------------|-------------|-------------------------|--------------------------|---------------------------|
| <b>20 lb. Bond, 92 Bright, 2" core</b> | RIJB11-4        | 11" x 150'  | 8/ctn                   | 13                       | 25                        |
|  | RIJB17-4        | 17" x 150'  | 4/ctn                   | 16                       | 25                        |

|  |            |            |       |    |    |
|--|------------|------------|-------|----|----|
|  | RIJB18-4   | 18" x 150' | 4/ctn | 16 | 25 |
|  | RIJB22-4   | 22" x 150' | 4/ctn | 19 | 25 |
|  | RIJB24-4   | 24" x 150' | 4/ctn | 22 | 25 |
|  | RIJB30-4   | 30" x 150' | 4/ctn | 27 | 25 |
|  | RIJB34-4   | 34" x 150' | 4/ctn | 30 | 25 |
|  | RIJB36-4   | 36" x 150' | 4/ctn | 32 | 25 |
|  | RIJB42-4   | 42" x 150' | 4/ctn | 44 | 25 |
|  | RIJB24-300 | 24" x 300' | 2/ctn | 42 | 25 |
|  | RIJB30-300 | 30" x 300' | 2/ctn | 52 | 25 |
|  | RIJB34-300 | 34" x 300' | 2/ctn | 60 | 25 |
|  | RIJB36-300 | 36" x 300' | 2/ctn | 62 | 25 |
|  | RIJB42-300 | 42" x 300' | 2/ctn | 72 | 25 |

**RIJT - 18 lb. Inkjet Translucent Bond**

**GEOMETRY:** 150 ft. and 300 ft. lengths. Widths vary 12" to 42". Core size is 2.0"

**PROPERTIES:** 18 lb./ 68 gsm, Opacity ≥ 69%, Brightness ~ 90.

**BEST PRINTING:** Use "light ink coverage" settings to match the paper coating to ensure proper ink volume and drying time. Remember to always print on the preferred side of the media. The preferred side is always on the outside of the roll unless otherwise noted. Handle print media by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° and 25-70% humidity. This paper can be used acceptably for pen plotting.

**STORAGE:** Always store inkjet media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**ARCHIVING:** 18# Inkjet Translucent Bond Is a wood pulp product and is not suitable for long term archival purposes.

Translucent Bond is the media of choice for combining the translucency of vellum, and the great value of ordinary bond paper. For non-archival purposes, our smooth, translucent stock is great for test plotting of print series on your inkjet plotter.

|                                | <b>Part No.</b> | <b>size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|--------------------------------|-----------------|-------------|-------------------------|--------------------------|---------------------------|
| <b>18 lb. Translucent Bond</b> | RIJT15-4        | 15" x 150'  | 4/ctn                   | 14                       | 25                        |
|                                | RIJT22-4        | 22" x 150'  | 4/ctn                   | 16                       | 25                        |
|                                | RIJT24-4        | 24" x 150'  | 4/ctn                   | 22                       | 25                        |
|                                | RIJT30-4        | 30" x 150'  | 4/ctn                   | 27                       | 25                        |
|                                | RIJT34-4        | 34" x 150'  | 4/ctn                   | 30                       | 25                        |
|                                | RIJT36-4        | 36" x 150'  | 4/ctn                   | 32                       | 25                        |
|                                | RIJT42-4        | 42" x 150'  | 4/ctn                   | 36                       | 25                        |
|                                | RIJT24-300      | 24" x 300'  | 2/ctn                   | 44                       | 25                        |
|                                | RIJT30-300      | 30" x 300'  | 2/ctn                   | 54                       | 25                        |
|                                | RIJT36-300      | 36" x 300'  | 2/ctn                   | 66                       | 25                        |

**RIJT-415 - 15 lb. Inkjet Translucent Bond**

**GEOMETRY:** 150 ft. Lengths. Widths vary 24" to 36". Core size is 2.0"

**PROPERTIES:** 15 lb./ 56 gsm. Opacity ≥ 69%, Brightness ~ 92.

**BEST PRINTING:** Use "light ink coverage" settings to match the paper coating to ensure proper ink volume and drying time. Remember to always print on the preferred side of the media. The preferred side is always on the outside of the roll unless otherwise noted. Handle print media by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° F and 20-70% humidity. This paper can be used acceptably for pen plotti

**STORAGE:** Always store inkjet media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**ARCHIVING:** 15 lb. Inkjet Translucent Bond is a wood pulp product and is not suitable for long term archival purposes.

Translucent Bond is the media of choice for combining the translucency of vellum, and the great value of ordinary bond paper. For non-archival purposes, our smooth, translucent stock is great for diazo reprinting and for test plotting of print series on your plotter.

|                                | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|--------------------------------|-----------------|-------------|-------------------------|--------------------------|---------------------------|
| <b>15 lb. Translucent Bond</b> | RIJT24-415      | 24" x 150'  | 4/ctn                   | 22                       | 25                        |
|                                | RIJT30-415      | 30" x 150'  | 4/ctn                   | 27                       | 25                        |
|                                | RIJT36-415      | 36" x 150'  | 4/ctn                   | 32                       | 25                        |

**RIJB-24 - 24 lb. Inkjet Color Bond**

**GEOMETRY:** 150 ft. and 300ft. lengths. Widths vary 11" to 42". Core is 2.0"

**PROPERTIES:** 24 lb. / 90 gsm, Opacity ≥ 88%, Brightness ~ 96.

**BEST PRINTING:** Use optimized settings to match the paper coating to ensure proper ink volume and drying time. Remember to always print on the preferred side of the media. The preferred side is always on the outside of the roll unless otherwise noted. Handle by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° and 25-70% humidity. This paper can be used acceptably for pen plotting.

**STORAGE:** Always store inkjet media in a cool area. If storage conditions vary from printing conditions allow the product to adjust before bringing to print.

**ARCHIVING:** 24# Inkjet Bond is a wood pulp product and is not suitable for long term archival purposes

24 lb. stock offers durability and opacity thanks to its heavy base. The specially coated surface provides superior image quality and color fastness for your color inkjet line and graphics plots demanding a high quality, long lasting finish.

|   | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|---|-----------------|-------------|-------------------------|--------------------------|---------------------------|
| <b>24 lb. Coated Bond, 96 Bright, 2" core</b> | RIJB18-424      | 18" x 150'  | 4/ctn                   | 20                       | 25                        |
|   | RIJB22-424      | 22" x 150'  | 4/ctn                   | 21                       | 25                        |

|  |              |            |       |    |    |
|--|--------------|------------|-------|----|----|
|  | RIJB24-424   | 24" x 150' | 4/ctn | 22 | 25 |
|  | RIJB30-424   | 30" x 150' | 4/ctn | 27 | 25 |
|  | RIJB34-424   | 34" x 150' | 4/ctn | 30 | 25 |
|  | RIJB36-424   | 36" x 150' | 4/ctn | 32 | 25 |
|  | RIJB42-424   | 42" x 150' | 4/ctn | 37 | 25 |
|  | RIJB36-24    | 36" x 150' | 1/ctn | 8  | 25 |
|  | RIJB54-24    | 54" x 150' | 1/ctn | 10 | 25 |
|  | RIJB60-24    | 60" x 100' | 1/ctn | 12 | 25 |
|  | RIJB24-24300 | 24" X 300' | 2/ctn | 24 | 25 |
|  | RIJB30-24300 | 30" X 300' | 2/ctn | 32 | 25 |
|  | RIJB36-24300 | 36" X 300' | 2/ctn | 40 | 25 |
|  | RIJB42-24300 | 42" X 300' | 1/ctn | 23 | 25 |

|   |               |            |       |    |    |
|---|---------------|------------|-------|----|----|
| <b>24 lb. Uncoated Color Bond, 92 Bright,<br/>2" core</b> | RIJB18-424S   | 18" x 150' | 4/ctn | 17 | 25 |
|   | RIJB24-424S   | 24" x 150' | 4/ctn | 22 | 25 |
|   | RIJB30-424S   | 30" x 150' | 4/ctn | 27 | 25 |
|   | RIJB34-424S   | 34" x 150' | 4/ctn | 30 | 25 |
|   | RIJB36-424S   | 36" x 150' | 4/ctn | 32 | 25 |
|   | RIJB42-424S   | 42" x 150' | 4/ctn | 37 | 25 |
|   | RIJB36-24300S | 36" x 300' | 2/ctn | 32 | 25 |

The following rolls are 27#, 36#, and 47# Inkjet Color Bond Rolls

| Part No.  | Size       | Rolls per Carton | Pounds per Carton | Cartons per Pallet |
|-----------|------------|------------------|-------------------|--------------------|
| RIJB24-27 | 24" x 150' | 1/ctn            | 7                 | 40                 |
| RIJB30-27 | 30" x 150' | 1/ctn            | 8                 | 40                 |
| RIJB36-27 | 36" x 150' | 1/ctn            | 9                 | 40                 |
| RIJB17-36 | 17" x 100' | 1/ctn            | 5                 | 40                 |
| RIJB24-36 | 24" x 100' | 1/ctn            | 7                 | 40                 |
| RIJB30-36 | 30" x 100' | 1/ctn            | 8                 | 40                 |
| RIJB36-36 | 36" x 100' | 1/ctn            | 10                | 40                 |
| RIJB42-36 | 42" x 100' | 1/ctn            | 12                | 40                 |
| RIJB54-36 | 54" x 100' | 1/ctn            | 16                | 40                 |
| RIJB60-36 | 60" x 100' | 1/ctn            | 18                | 40                 |
| RIJB24-47 | 24" x 100' | 1/ctn            | 7                 | 40                 |
| RIJB30-47 | 30" x 100' | 1/ctn            | 8                 | 40                 |
| RIJB36-47 | 36" x 100' | 1/ctn            | 9                 | 40                 |
| RIJB42-47 | 42" x 100' | 1/ctn            | 10                | 40                 |
| RIJB54-47 | 54" x 100' | 1/ctn            | 12                | 40                 |
| RIJB60-47 | 60" x 100' | 1/ctn            | 13                | 40                 |

**RIJV-17 - 17 lb. Inkjet Vellum**

**GEOMETRY:** 150 ft. lengths. Widths may vary 22" to 42". Core size is 2.0"

**PROPERTIES:** 17 lb. / 64 gsm, Opacity ≥ 42%, Brightness ~ 96.

**BEST PRINTING:** Use "light ink coverage" settings to match the paper coating to ensure proper ink volume and drying time. Remember to always print on the preferred side of the media. The preferred side of the media is always on the outside of the roll unless otherwise noted. Handle the print area by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° and 25-70% humidity. This paper can be used acceptably for pen plottin

**STORAGE:** Always store inkjet media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**ARCHIVING:** 17# Inkjet Vellum is produced from 15% cotton fiber and is well suited for long term archivability in moderate environmental conditions.

Modern paper technology has created our awesome inkjet vellum. Our 15% cotton fiber base is transparentized with environmentally friendly solvents, and surface treatment is applied to produce an extremely smooth faced sheet with excellent ink acceptance. Lines and graphics come out clear, sharp and dense with no bleeding edges or running ink.

| 17 lb. Vellum, 2" core | Part No.  | Size       | Rolls per Carton | Pounds per Carton | Cartons per Pallet |
|------------------------|-----------|------------|------------------|-------------------|--------------------|
|                        | RIJV24-17 | 24" x 150' | 1/ctn            | 4                 | 40                 |
|                        | RIJV30-17 | 30" x 150' | 1/ctn            | 5                 | 40                 |
|                        | RIJV34-17 | 34" x 150' | 1/ctn            | 5.5               | 40                 |
|                        | RIJV36-17 | 36" x 150' | 1/ctn            | 6                 | 40                 |
|                        | RIJV42-17 | 42" x 150' | 1/ctn            | 8                 | 40                 |

**RIJV - 20 lb. Inkjet Vellum**

**GEOMETRY:** 150 ft. lengths. Widths vary 22" to 42". Core size is 2.0"

**PROPERTIES:** 20 lb. / 75 gsm. Opacity ≥ 50%, Brightness ~ 96.

**BEST PRINTING:** Use "light ink coverage" settings to match the paper coating to ensure proper ink volume and drying time. Remember to always print on the preferred side of the media. The preferred side of the media is always on the outside of the roll unless otherwise noted. Handle the print area by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° and 25-70% humidity. This paper can be used acceptably for pen plottin

**STORAGE:** Always store inkjet media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**ARCHIVING:** 20# Inkjet Vellum is produced from 15% cotton fiber and is well suited for long term archivability in moderate environmental conditions.

Modern paper technology has created our awesome inkjet vellum. Our 15% cotton fiber base is transparentized with environmentally friendly solvents, and surface treatment is applied to produce an extremely smooth faced sheet with excellent ink acceptance. Lines and graphics come out clear, sharp and dense with no bleeding edges or running ink. Our 20 lb. inkjet vellum has enhanced durability over our lighter 17 lb. product

| <b>20 lb. Vellum, 2" core</b> | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|-------------------------------|-----------------|-------------|-------------------------|--------------------------|---------------------------|
|                               | RIJV22          | 22" x 150'  | 1/ctn                   | 4                        | 40                        |
|                               | RIJV24          | 24" x 150'  | 1/ctn                   | 5                        | 40                        |
|                               | RIJV30          | 30" x 150'  | 1/ctn                   | 7                        | 40                        |
|                               | RIJV34          | 34" x 150'  | 1/ctn                   | 8                        | 40                        |
|                               | RIJV36          | 36" x 150'  | 1/ctn                   | 9                        | 40                        |
|                               | RIJV42          | 42" x 150'  | 1/ctn                   | 10                       | 40                        |

**20 lb. Vellum, Sheets**

|  |          |           |         |    |    |
|--|----------|-----------|---------|----|----|
|  | SIJV2436 | 24" x 36" | 400/ctn | 47 | 24 |
|--|----------|-----------|---------|----|----|

**RIJF - 4 Mil. Double Matte Film**

**GEOMETRY:** 125 ft. lengths. Widths vary 22" to 42". Core size is 2.0"

**PROPERTIES:** 4.0 mil, Opacity ≥ 45%

**BEST PRINTING:** Use "light ink coverage" settings to match the paper coating to ensure proper ink volume and drying time. Remember to always print on the preferred side of the media. The preferred side of the media is always on the outside of the roll unless otherwise noted. Handle the print area by the edges to prevent dirt and oils from contaminating the print area. Best results are achieved when operating at 65-85° and 25-70% humidity. This paper can be used acceptably for pen plottin

**STORAGE:** Always store inkjet media in a cool dry area. If storage conditions vary from printing conditions, allow the product to adjust before beginning to print.

**ARCHIVING:** 4 mil Inkjet Double Matte Film is produced from 100% synthetic polyester and is well suited for long term archivability in moderate environmental conditions.

Our double matte film is created from dimensionally stable polyester film held to tight tolerances. The specially coated surface offers exceptional inkjet line quality/uniformity and fast monochrome ink drying times. Monochrome images are virtually indestructable on our durable, archiveable poly: matte. Low opacity means rapid diazo reprints.

| <b>4 Mil. Double Matte Film, 2" core</b> | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|--|-----------------|-------------|-------------------------|--------------------------|---------------------------|
|  | RIJF22          | 22" x 125'  | 1/ctn                   | 6                        | 40                        |
|  | RIJF24          | 24" x 125'  | 1/ctn                   | 7                        | 40                        |
|  | RIJF30          | 30" x 125'  | 1/ctn                   | 8                        | 40                        |
|  | RIJF34          | 34" x 125'  | 1/ctn                   | 9                        | 40                        |
|  | RIJF36          | 36" x 125'  | 1/ctn                   | 10                       | 40                        |
|  | RIJF42          | 42" x 125'  | 1/ctn                   | 18                       | 40                        |

**4 Mil. Clear Double Matte Film, 2" core**

|  |            |           |       |    |    |
|--|------------|-----------|-------|----|----|
|  | RIJF36-4MC | 36" x 75' | 1/ctn | 10 | 40 |
|--|------------|-----------|-------|----|----|

**RIJF-3DM - 3 Mil. Double Matte Film**

**GEOMETRY:** 125 ft. lengths. Widths vary 24" to 36". Core is 2.0"

**PROPERTIES:** 3.3 Mil, Opacity ≥ 45%, Sheffield Smoothness 120

**BEST PRINTING:** Inkjet Film works best in controlled operating conditions. Recommended operating conditions are: Relative humidity 20-70% and temperature 65-85° F. Dry time for your image will vary depending on the printer, ink volume and environmental conditions of your plotting area.

**STORAGE:** Always store your inkjet media in a cool dry area. It is best to keep your storage conditions within the same guidelines as "Operating Conditions" stated above. If your storage conditions are not similar to operating conditions, we recommend that you allow the media to acclimate to the operating conditions before the printing process. Remember to always print on the preferred side of the media. The preferred side of the media is always on the outside of the roll unless otherwise noted. Handle the print media by the edges to prevent dirt and oils from contaminating the print area.

**ARCHIVING:** Durability Polyester base leaves images virtually indestructable. Proprietary Top Coat allows for crisp, clear ink acceptance.

**ERASING:** When erasing the inkjet coated side (preferred side) of inkjet film, we suggest a moistened eraser using a "light touch" of rubbing. Rubbing too hard can remove the matte surface. The matte on the reverse side is perfect for multiple drafting revisions.

**3 Mil. Double Matte Film, 2" core**

|  | <b>Part No.</b> | <b>Size</b> | <b>Rolls per Carton</b> | <b>Pounds per Carton</b> | <b>Cartons per Pallet</b> |
|--|-----------------|-------------|-------------------------|--------------------------|---------------------------|
|  | RIJF24-3DM      | 24" x 125'  | 1/ctn                   | 7                        | 40                        |
|  | RIJF30-3DM      | 30" x 125'  | 1/ctn                   | 8                        | 40                        |
|  | RIJF36-3DM      | 36" x 125'  | 1/ctn                   | 10                       | 40                        |

**PRODUCTS BELOW ARE IN THE SUPPORT BINDER**



**POSTER PAPERS**

| DESCRIPTION                      | SIZE       |                | MSRP<br>(per roll) |
|----------------------------------|------------|----------------|--------------------|
| <b>7 MIL PREMIUM PHOTO PAPER</b> | 24" x 100' | Available in   | 54.00              |
|                                  | 36" x 100' | Satin or Gloss | 80.00              |
|                                  | 42" x 100' |                | 96.00              |
|                                  | 44" x 100' |                | 96.00              |
|                                  | 50" x 100' |                | 112.00             |
|                                  | 60" x 100' |                | 134.00             |

|   |            |                |        |
|---|------------|----------------|--------|
| <b>8 MIL UNIVERSAL PHOTO PAPER</b><br>Quick Dry | 24" x 100' | Available in   | 84.00  |
|   | 36" x 100' | Satin or Gloss | 125.00 |
|   | 42" x 100' |                | 150.00 |
|   | 44" x 100' |                | 150.00 |
|   | 50" x 100' |                | 174.00 |
|   | 60" x 100' |                | 209.00 |

**SIGN MATERIALS - MATTE**

|  |           |           |        |
|--|-----------|-----------|--------|
| <b>4 MIL PRESSURE SENSITIVE ADHESIVE</b><br>water resistant, non-glare PVC vinyl | 24" x 60' | Permanent | 97.00  |
|  | 36" x 60' | or        | 145.00 |
|  | 42" x 60' | Removable | 174.00 |
|  | 44" x 60' | PSA       | 174.00 |
|  | 50" x 60' |           | 202.00 |
|  | 60" x 60' |           | 242.00 |

|  |           |  |        |
|--|-----------|--|--------|
| <b>15 MIL SMOOTH SCRIM BANNER</b><br>water-resistant, non-glare finish | 24" x 40' |  | 87.00  |
|  | 36" x 40' |  | 130.00 |
|  | 42" x 40' |  | 156.00 |
|  | 44" x 40' |  | 156.00 |
|  | 50" x 40' |  | 181.00 |
|  | 60" x 40' |  | 217.00 |

|   |           |  |        |
|---|-----------|--|--------|
| <b>11 MIL VALERON BANNER</b><br>water-resistant, non-glare finish | 24" x 75' |  | 117.00 |
|   | 36" x 75' |  | 175.00 |
|   | 42" x 75' |  | 210.00 |
|   | 44" x 75' |  | 210.00 |
|   | 50" x 75' |  | 244.00 |
|   | 60" x 75' |  | N/A    |

|  |           |  |        |
|--|-----------|--|--------|
| <b>14 MIL ECONOMY SCRIM</b><br>water-resistant, non-glare finish | 24" x 75' |  | 99.00  |
|  | 36" x 75' |  | 148.00 |
|  | 42" x 75' |  | 177.00 |
|  | 44" x 75' |  | 177.00 |
|  | 50" x 75' |  | 206.00 |
|  | 60" x 75' |  | 247.00 |

|   |            |  |        |
|---|------------|--|--------|
| <b>8 MIL BOPP</b><br>Polypropylene Film<br>water/tear resistant, non-glare finish | 24" x 100' |  | 64.00  |
|   | 36" x 100' |  | 95.00  |
|   | 42" x 100' |  | 114.00 |
|   | 44" x 100' |  | 114.00 |
|   | 50" x 100' |  | 132.00 |
|   | 60" x 100' |  | 159.00 |

|   |           |  |        |
|---|-----------|--|--------|
| <b>11 MIL BLOCKOUT PE BANNER</b><br>water-resistant, smooth, non-glare finish | 24" x 90' |  | 124.00 |
|   | 36" x 90' |  | 185.00 |
|   | 42" x 90' |  | 257.00 |
|   | 44" x 90' |  | 257.00 |
|   | 50" x 90' |  | 257.00 |
|   | 60" x 90' |  | 309.00 |

**SIGN MATERIALS - GLOSS**

|  |           |                  |        |
|--|-----------|------------------|--------|
| <b>4 MIL PRESSURE SENSITIVE ADHESIVE</b> | 24" x 60' | <b>Permanent</b> | 117.00 |
| <b>PVC vinyl with high-gloss finish</b>  | 36" x 60' | <b>or</b>        | 175.00 |
| <b>water resistant</b>                   | 42" x 60' | <b>Removable</b> | 210.00 |
|  | 44" x 60' | <b>PSA</b>       | 210.00 |
|  | 50" x 60' |                  | 244.00 |
|  | 60" x 60' |                  | 292.00 |

**FINE ART CANVAS**

|  |           |                     |        |
|--|-----------|---------------------|--------|
| <b>23 MIL 100% COTTON CANVAS</b>         | 17" x 40' | <b>Matte Finish</b> | 51.00  |
| <b>water resistant, non-glare finish</b> | 24" x 40' |                     | 97.00  |
|  | 36" x 40' |                     | 145.00 |
|  | 42" x 40' |                     | 170.00 |
|  | 44" x 40' |                     | 170.00 |
|  | 50" x 40' |                     | 202.00 |
|  | 60" x 40' |                     | 242.00 |

|  |           |                     |        |
|--|-----------|---------------------|--------|
| <b>22 MIL POLYCOTTON BLEND CANVAS</b>    | 17" x 40' | <b>Matte Finish</b> | 51.00  |
| <b>water resistant, non-glare finish</b> | 24" x 40' |                     | 97.00  |
|  | 36" x 40' |                     | 145.00 |
|  | 42" x 40' |                     | 170.00 |
|  | 44" x 40' |                     | 170.00 |
|  | 50" x 40' |                     | 202.00 |
|  | 60" x 40' |                     | 242.00 |